




## LIGHT WEIGHT / ECONOMIC E-PUMP

### **PU20M3N01B / PU20M4N01B / PU20DMP01B**



#### Features:

- Light Weight and compact mechanism design
- Compares to Enerpac PUJ-1201B / PUJ-1401B
- 115VAC 50/60 HZ Universal Motor, starts under full load
- 10', 24 VAC pendant control for safety
- For use with generators or extension cords
- Designed for intermittent duty cycle.



\* shown with optional external pressure adjustment knob



|                                                               | Enerpac PUJ-1401B                                  | BVA PU20M4N01B                                   |
|---------------------------------------------------------------|----------------------------------------------------|--------------------------------------------------|
| <b>Usable Oil</b>                                             | 1 Gal.                                             | 1 Gal.                                           |
| <b>Reservoir Material</b>                                     | Plastic Reservoir                                  | Steel Reservoir                                  |
| <b>Flow Rate @ Low Pressure</b>                               | 200 Cu. In. @ 200 PSI                              | 133 Cu. In. @ 200 PSI (Measured)                 |
| <b>Flow Rate @ High Pressure</b>                              | 20 Cu. In. @ 10,000 PSI                            | 28 Cu. In. @ 10,000 PSI (Measured)               |
| <b>1<sup>st</sup> / 2<sup>nd</sup> Stage Pressure Setting</b> | 200 PSI / 10,000 PSI                               | 1,200 PSI / 10,000 PSI                           |
| <b>Control Valve</b>                                          | 4 Way / 3 Pos.                                     | 4 Way / 3 Pos.                                   |
| <b>Motor Type</b>                                             | Universal                                          | Universal                                        |
| <b>Horse Power</b>                                            | 1.2 HP (0.9 KW)<br>0.5 HP (Catalog Shown)          | 0.94 HP (0.7KW)<br>1.0 HP                        |
| <b>Current Draw</b>                                           | 9.5 A (@10000 PSI)                                 | 10.0 A (@10,000 PSI)                             |
| <b>Motor Voltage</b>                                          | 115 VAC, 50/60 Hz                                  | 115 VAC, 50/60 Hz                                |
| <b>Sound Level</b>                                            | 85 - 89 dBA                                        | 80 - 85 dBA                                      |
| <b>Net Weight</b>                                             | 44 Lbs (w/ plastic reservoir)<br>1 Gal. usable oil | 37 Lbs (w/ metal reservoir)<br>1 Gal. usable oil |

#### SFA Companies

10939 N. Pomona Ave. • Kansas City, MO 64153 • Tel: 816-891-6390 Fax: 816-448-2142  
www.bvahydraulics.com • Email: sales@bvahydraulics.com